



## LED Flashlight BML802

Satisfy Professional's Needs

**LXT**  
LITHIUM-ION

**18V**  
LITHIUM-ION

**14.4V**  
LITHIUM-ION



Battery is option.

# HIGH LUMINANCE 3.2W LED



# Long continuous illumination of 13 hours

with a fully charged 18V-3.0Ah battery BL1830

## 12 Position pivoting flashlight head

Positive stops at 110°, 90°, 75°, 60°, 45°, 30°, 15°, 0°, -15°, -30°, -45°, -60°



## Light source

Type : 3.2W single LED  
Illuminance : 4,000lx  
Luminous flux : 160lm  
Service life : 50,000hours or more



Illuminance: measured in ø20mm circle at the center of an illuminated field 1m in front of the light source.

## Multi-faceted reflector

controls the direction and spread of light cast from LED to provide a sharp round spot light with uniform high brightness.



## Strap hook

can be installed on the upper or lower position in accordance with usage.



## Compact size aluminum flashlight head

gives an impression of heavy-duty product.

Ergonomically designed handle with rubberized soft grip

On/Off switch



Battery is option.

## Battery



BL1830: 18V 3.0Ah  
BL1815: 18V 1.3Ah  
BL1430: 14.4V 3.0Ah  
BL1415: 14.4V 1.3Ah

## Charger

DC18RC / DC18RA  
Charging time  
22minutes



DC18SD  
Charging time  
60minutes



## LED Flashlight

## BML802 18V, 14.4V

	18V LITHIUM-ION	14.4V LITHIUM-ION
<b>Continuous use (hours)</b>	13-3.0Ah, 6-1.3Ah	9-3.0Ah, 4-1.3Ah
<b>Dimensions (L x W x H)</b>	272x79x116mm (10-3/4"x3-1/8"x4-9/16") with BL1830 256x79x116mm (10-1/8"x3-1/8"x4-9/16") with BL1815	272x79x99mm (10-3/4"x3-1/8"x3-7/8") with BL1430 256x79x99mm (10-1/8"x3-1/8"x3-7/8") with BL1415
<b>Net Weight*</b>	0.93kg (2.1lbs) with BL1830 0.71kg (1.6lbs) with BL1815	0.84kg (1.9lbs) with BL1430 0.65kg (1.5lbs) with BL1415
<b>Standard Equipment :</b> Strap hook, Battery and Charger are sold separately.		

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BC-AH